



Plastic Tank



S.S. Tank

ULV COLD FOGGER

TECHNICAL FEATURES

- UL & CE approved powerful turbo motors deliver 60% more power & spread than any other system.
- Offers greater reliability and longer life.
- Made of high strength non corrosive engineering plastics & stainless steel.
- Adheres to clean rooms hygiene standards.
- Electric shock proof and unbreakable motor housing.

APPLICATIONS AREAS

Aerial disinfection in hospitals	:	Operation theaters, ICU, clinics.
Laboratories	:	Microbiology, tissue culture.
Sterile areas	:	Pharmaceutical industry.
Sanitation treatment	:	Food & Beverage processing plants, dairies, kitchens.
Infection prevention	:	Poultry, hatcheries, animal houses. Veterinary Clinics.
Pest control treatment	:	Commercial and industrial areas.
Deodorizing treatment	:	Hotels, food plants.
Anti mole Sanitizer	:	Residential & commercial applications



Specifications :

Power Supply	:	220V AC, 50 or 60 hz
Aerosols	:	Submicron size
Spray Particle Size	:	3 – 10 Microns
Spread & Reach	:	40 ft. distance & 20.ft. height
Space Treatment	:	Upto 9000 cu. ft.
Treatment of 100 sq. ft. area	:	400ml. disinfectant solution
Nozzle Assembly	:	Non clogging design- Stainless Steel cap and barrel
Precision Metering System	:	0-80 ml/ minute (Adjustable)
Solution Tank & Lid	:	5 Litre Stainless Steel Gr. 304 (Autoclavable) Liquid Filling Nipple - SS 304 Or Engg. Plastics Tank Set 5 Ur. Capacity with Graduated Markings Tank Gasket - Silicon Grade
Silicon Tubing	:	Complies to FDA & USP CLASS VI.
Machine Handle	:	Stainless Steel
Mounting Ring	:	Stainless Steel
Strainer	:	Stainless Steel
Liquid Line Connectors	:	Stainless Steel
Hardware	:	Stainless Steel
Intake Air Filter	:	Uniquely designed Two layers for dust & fog separation
Machine Weight	:	7.2 kg portable. (with SS Tank set)
Machine Weight	:	6.0 kg portable. (with Plastic Tank set)